©OUTLANDER™ X® mr 1000R

HIGHLIGHTS

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- Front and rear FOX† PODIUM† 1.5 QS3 shocks
- 30-in. ITP Cryptid† tires
- 14-in. cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS™)
- · Relocated radiator
- 3,000-lb (1,361 kg) WARN[†] winch with roller fairlead
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with wind deflectors and square pad
- Mud-riding footrests

Rear Shocks

- 59-in. wheelbase
- Multifunction Analog / Digital gauge
- X-package coloration, graphics and seat cover



Gold, Black & Can-Am Red / 1000R Sunburst Yellow / 1000R

ENGINE	1000R
Туре	91 hp, Rotax 976 cc V-twin, snorkeled, liquid cooled with relocated radiator
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

Power Steering	Tri-Mode Dynamic Power Steering (DPS)		
SUSPENSIONS			
Front Suspension	Arched double A-arm with front sway bar		
Front Shocks	FOX 1.5 PODIUM QS3		
Rear Suspension	Torsional Trailing arm Independent (TTI)		

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

FOX 1.5 PODIUM QS3

TIRES / WHEELS	
Front Tires	ITP Cryptid [†] 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid [†] 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Wheels	14-in. cast-aluminum

DIMENSIONS / CAPACITIES		
97 x 50 x 51.5 in. (246 x 127 x 131 cm)		
59 in. (149.9 cm)		
13 in. (33 cm)		
36.75 in. (93.3 cm)		
1020 lb (464 kg)		
Rear: 200 lb (90 kg)		
Rear: 5.7 gal (21.4 L)		
1,650 lb (750 kg)		
5.4 gal (20.5 L)		

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Standard
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front & rear bumpers, aluminum taper-profile handlebar with wind deflectors and square pad, mud-riding footrests and mudguards		

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage



